

KromaKrete™ System

UV-Stable Lithium Colored Hardener



383 Canterbury Road Surrey Hills 3127

TEL: 61 3 9836 4488

SALES / TECH SUPPORT: 0411 248 486

www.sealsourceaustralia.com

LEED® EQ Credit 4.1: Low-Emitting Materials: Adhesives & Sealants

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

KromaKrete™ is a non-polishable concrete-coloring system that provides superior stain resistance in addition to the benefits of a penetrating hardener/densifier. The material penetrates the surface to bond to the substrate, protecting against abrasion and dusting. When used with **DuraGloss™** as recommended, the **KromaKrete™** system creates a durable, UV-stable surface that is easy to clean and maintain—dramatically reducing maintenance costs and downtime. The unmatched protection of the **KromaKrete™** system outlasts any product of its kind in the industry.

COLORS

KromaKrete™ is available in thirteen standard, in-stock colors. (Custom colors are available upon request.) Please understand that the colors portrayed in our product literature are the closest representation possible, however color may vary depending on the condition of the concrete being treated. We recommend the application of a physical sample prior to treating the entire surface.

USES

The **KromaKrete™** system is designed for interior or exterior use and may be used in virtually any industrial or commercial environment where a colored surface is desired, such as restaurants, retail stores, schools, office buildings, shopping centers, hotels, grocery stores, theaters, manufacturing facilities, distribution centers, transportation terminals, convention centers, and sports & entertainment venues.

ADVANTAGES

- UV-Stable
- Light Reflective
- Odorless
- Deep penetration for maximum durability
- Superior stain resistance
- Protects against abrasion and dusting
- Superior durability reduces maintenance costs and downtime



- Meets and Exceeds OSHA and ADA coefficient of friction
- Easy to clean and maintain

PHYSICAL PROPERTIES

Form:	various colors, aqueous solution
Total Solids:	23%
Active Ingredients:	100% of total solids
Specific Gravity:	1.09
pH Level:	11.5
Flash Point:	N/A
VOC Content:	< 50gms/L
Freeze Point:	0° C (32° F)
Abrasion Resistance:	Excellent
Depth of Surface Penetration:	2-8 mm

PACKAGING

- 55 Gallon Drums (drum containers filled by weight, volume is closely approximate)
- 5 Gallon Pails

MIXING

KromaKrete™ is a single component product. Mechanically stir for 5-10 minutes prior to use.

APPLICATION METHOD/COVERAGE RATE

Please see separate application instruction document for complete application information.

KromaKrete™ may be applied by a low pressure sprayer, airless sprayer or rolled on and worked in with a broom. A minimum of two coats should be applied at 10-15 m²/liter (400-600 sq.ft/gallon).

SHELF LIFE

KromaKrete™ may be stored for up to six months in original, unopened factory containers under normal storage conditions of 13° – 35° C (55°-95° F).

SAFETY

- Read Material Safety Data Sheet before using
- Keep out of reach of children
- Protect from freezing
- Wear safety glasses and rubber gloves
- Do not apply to soft metals
- Do not apply to glass

WARRANTY

SealSource® International LLC, will refund the price of or replace, at its election, product it finds to be defective provided the product has been used properly. Except as expressly stated above, the Company makes no warranty of merchantability and no warranty of fitness for any particular purpose, nor does it

make any warranty, expressed or implied, of any nature whatsoever with respect to the product or its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special or consequential damages, or for any charges or expenses of any nature incurred without its written consent.